

Method and apparatus for making picture display device

Patent number: CN1312536 (A)

Publication date: 2001-09-12

Inventor(s): SHUNGEN MIYASAKI [JP]; KOJI NAKATA [JP]; TETSUYA KANEKO [JP]

Applicant(s): CANON KK [JP]






Classification:

- international: H01J9/39; H01J9/18; H01J9/26; H01J9/33; H01J9/40; H01J9/46; H01J9/48; H01J9/00; H01J9/18; H01J9/26; H01J9/38; (IPC1-7): G09G3/30; H01J9/26; H01J9/38
 - european: H01J9/18; H01J9/38; H01J9/48

Application number: CN20011016873 20010216

Priority number(s): JP20000038603 20000216

Also published as:


 CN100430981 (C)
 EP1126496 (A2)
 EP1126496 (A3)
 US2001034175 (A1)
 US5905384 (B2)

more >>

Abstract not available for CN 1312536 (A)

Abstract of correspondent EP 1126496 (A2)

A method and an apparatus for manufacturing an image displaying apparatus having a display panel are provided. A first substrate of the display panel on which phosphor exciting means is disposed and a second substrate of the display panel on which phosphors emitting light by the phosphor exciting means is provided are prepared under the vacuum atmosphere. Then, the first and the second substrates are carried in a getter processing chamber or bake processing chamber, and getter processing or bake processing is applied thereto under the vacuum atmosphere. After the processing, the first and the second substrates are carried in a seal processing chamber, where the substrates are heat sealed under the vacuum atmosphere. Thus, reduction of vacuum exhaust time and a high vacuum degree in manufacturing an image displaying apparatus is attained and efficiency of manufacturing is improved.



Data supplied from the esp@canet database — Worldwide